

Sales Team Analytics

Your contacts

Andreas Horst

Global Key Account Manager

Fon +49 (7142) 583-258

Mobil +49 172 7825482

E-Mail andreas.horst@elringklinger.com



Werner Hartwig

Field Sales Manager

Fon +49 (7142) 583-251

Mobil +49 151 23621246

E-Mail werner.hartwig@elringklinger.com



How to find us

Global. Regional. Local.



ElringKlinger Kunststofftechnik GmbH

Your specialist in Engineered Plastics

Etzelstraße 10
D-74321 Bietigheim-Bissingen

Fon +49 7142 583-0

Fax +49 7142 583-200

E-Mail lifescience@elringklinger.com

www.elringklinger-engineered-plastics.com



<https://www.elringklinger-engineered-plastics.com/industries/medical-life-science/analytics/>

The information is non-binding and does not represent any warranted characteristics.
Any claims for compensation based on this information cannot be accepted.
No guarantee for printing errors.

Analytics



ElringKlinger Engineered plastics
We take you ahead!

elringklinger
Engineered Plastics

Our core competencies for Analytics

Manufacturing to the highest standards

Our material



PTFE tubings for liquid transport in the field of liquid chromatography (LC)



Seals for use in high-pressure pumps in HPLC applications



Porous PTFE for filtering liquids or reducing noise



Degassing modules for degassing of analytical liquids



Optical PTFE for light measurement applications

Complete production process from semi-finished product to finished product.

- Material development and compounding in-house
- Extrusion
- Injection molding
- Machining
- Clean room production
- Hygienic design (CIP, SIP)
- Production of complex assemblies

Certificates:

- EN ISO 13485
- ISO 9001
- GMP
- DIN EN ISO 14001
- ISO 50001



High-performance plastics are the best material choice for metering or handling fluids of different chemical natures at diverse temperatures and pressures. Based on your requirements, we offer a wide range of materials:

High performance plastics:

- PTFE
- PEEK
- PFA
- FEP
- Moldflon®-materials

Characteristics:

- Highest bending strength / long service life
- High temperature resistance
- Almost universal chemical resistance
- Physiologically harmless
- Anti-adhesive properties

Approvals:

- REACH
- FDA
- BAM
- DVGW
- EU 10/2011, EG 1935/2004
- GMP (Good Manufacturing Practice)